

# JALWENGE 00JJE70

S3S SC CI LG FO SR  
EN ISO 20345:2022  
38 to 47

# Softane Adventure



QuickLio™



- Water-repellent full-grain leather
- Dual density **Softane™** sole
- Polymère toe cap type **B** and no metallic midsole **S**
- Antistatic and amagnétique

- Safety shoe rangers type with minimal stitching for improved resistance. Black color.
- Water-repellent full grain leather upper, thickness 1.9/2.1 mm. Black colour.
- The polyurethane toe cap, having been **SC**-rated, complies with EN ISO 20345:2021, which guarantees the footwear's sturdiness and longevity, as well as its increased resistance to impacts and scuffing.
- Upper lined in breathable **3D Surf** mesh with honeycomb structure to improve the peripheral ventilation of the foot, dries out rapidly.
- Padded ergonomic collar in compact flexible foam for extra comfort and better ankle and Achilles tendon protection.
- Padded leather tongue for good instep protection, combined with two side bellows to prevent any dirt from getting into the boots.
- Lace up by five pairs of non-metallic lace-stays and two pairs of **Quick LIO** (Quick Lace In Out).  
Water-repellent laces : 130 cm.
- Soft** footbed made of **BASF Dynamic polyurethane** with heat sensitive memory foam and acts over the entire surface of the foot, cushions pressure points, improves weight distribution and shock absorption caused by impact with the ground. Anatomical, breathable.
- The **FleXtane™ S-type** mounting insole by Jallatte is puncture-resistant to sharp objects up to **3mm in diameter (Small)** in compliance with standard **22568-4:2021**, antistatic, 100% composite, sewn directly onto the upper and covers 100% of the foot for all-round protection.
- Ergonomic shoe with broad toe-cap **SPRINGTANE type B** polymer tip for weight savings (50% lighter than steel). Resistant to a shock of 200 Joules. Minimum height after test  $\geq 4$ mm in relation to the Type A toe cap in accordance with Standard 22568-2:2019.
- Heel stiffener to reinforce the heel seat.
- Dual density **Softane™ PU** sole, **robust and versatile**, with progressive shock absorber and anti-twist heel reinforcement integrated. Pu reinforcement to the front of the sole. Sole features with the **JAL'GRIP SYSTEM**, a LADDER GRIP double-release unhooking system as standard, is fully LG-rated in compliance with standard EN ISO 20345:2021, which enables ladder attachment and prevents the risk of falls from heights.



**Slip resistance tests results EN Standard ISO 20345:2022**

Test ground : Ceramic / NaLS (Sodium lauryl sulfate)  
A- Heel to the front **0,36** ( $\geq 0,31$ )  
B- Front to back **0,42** ( $\geq 0,36$ )

**Additional requirement SR** : Ceramic /Glycerin  
C - Heel to the front **0,23** ( $\geq 0,19$ )  
D- Front to back **0,33** ( $\geq 0,22$ )

- Softane™ comfort layer, density 0.45 / Outsole density = 1.10.
- High abrasion resistance .
- Highly resistant to oils and hydrocarbons.
- Heel shock absorbtion > 20 Joules.
- Rugged sole pattern with self-cleaning treads, depth 6,5 mm.
- Very flat sole with a large contact area with the ground. Improved stability.

Weight	Gross weight (42) : 1716 g / Net weight (42) : 1500 g	
Size	35 à 45	46 au 48
Packaging	5 pairs	
Box shoes (mm)	337 x 328 x 135	365 x 320 x 134
Cartons (mm)	625 x 425 x 343	690 x 330 x 383

