



02 FO SRC
EN ISO 20347:2012
35 to 48



Link-ESD



ASSEMBLÉ
EN
FRANCE



0%
METAL

Work sneakers for professional use
(No toe cap, no anti-perforation)

- ❖ Work sneakers for professional use, designed with **anti-fatigue technology**, no toe cap or anti-perforation sole. Upper and sole assembled in France. White and grey color.
- ❖ Safety shoe protecting the electronic devices against electrostatic discharge phenomena. Electrostatic dissipative shoes **ESD** Environmental Class II tested according to **EN 61340-4-3/4-5/5-1**.
- ❖ **Putek® PLUS** textile upper, high resistance to abrasion, water repellent and breathable. Anti abrasion insert. **TPU insert** built-in to the laces, ensuring an effective heel grip, enhanced alignment of the foot in the shoe and protection against any sprains.
- ❖ Upper lined in breathable **3D Surf** mesh with honeycomb structure to improve the peripheral ventilation of the foot, dries out rapidly.
- ❖ Padded tongue for good instep protection, combined with two side bellows to prevent any dirt from getting into the shoe.
- ❖ Padded ergonomic collar in compact flexible foam, lined for extra comfort and better ankle and Achilles tendon protection.
- ❖ **Xtensible™** Quicklace fastening system with no lacing: elastic lace fitted with an adjustable **Stop-Lace** quick tight lace.
- ❖ **Soft+ Gel** footbed made of **BASF Dynamic polyurethane** with heat sensitive memory foam and acts over the entire surface of the foot, cushions pressure points, improves weight distribution and shock absorption caused by impact with the ground. Anatomical, breathable and fitted with the **Link ESD™** system, an innovative and seamless, multi-contact static electricity dissipater (Patent pending).
- ❖ This is a **DGUV 112-191** certified model, with the option of swapping the hygienic insole provided for a **SECOSOL®** orthopaedic insole.
- ❖ Heel stiffener to reinforce the heel seat.
- ❖ **Innovative J-Energy sole** in bi-ingredient **PU** / and **BASF Infinergy® E-TPU** (Expanded Thermoplastic PolyUrethane) insert, with a remarkable capacity to reproduce more than **55%** of the energy accumulated while walking in order to reduce fatigue and to prevent RSIs to the legs.



Slip resistance tests results EN Standard ISO
20345:2011

SRA Test ground : Ceramic / Lauryl Sulfate

A- Heel to the front **0,62 (>0,32)**

B- Front to back **0,48 (>0,28)**

SRB : Ceramic / Glycerin

C - Heel to the front **0,23 (>0,18)**

D- Front to back **0,19 (>0,13)**

➤ Polyurethane outer sole.

➤ **E-TPU insert** at low density of 0.25.

- As elastic as rubber but lighter.
- High resistance to abrasion and stretching.
- Good chemical resistance.
- Long-term durability in a wide temperature range.

Dynamic performance in 3 phases : Shock Absorption – Accumulation of energy - Dynamic Return

Infinergy®

Made with Infinergy® by BASF

Weight	Gross weight (42) : 1116 g / Net weight (42) : 900 g			
Size	35 to 39	40 to 42	43 to 45	46 to 48
Packaging	5 pairs	10 pairs		5 pairs
Boites (mm)	340 x 210 x 133		340 x 245 x 133	
Box shoes (mm)	687 x 226 x 350	687 x 432 x 348	689 x 511 x 351	689 x 226 x 351



www.jallatte.com