

JOJ0213 JALLABO ESD



* Brevet International



02 FO SRC
EN ISO 20347:2012
35 to 48



ASEPTANE
Link-ESD

ASSEMBLÉ
EN
FRANCE



Work sneakers for professional use
(No toe cap, no anti-perforation)

- ❖ Flexible and lightweight work shoe, without toe cap or anti-perforation sole, designed with anti-fatigue technology. Upper and sole assembled in France. white and grey color.
- ❖ Safety shoe protecting the electronic devices against electrostatic discharge phenomena. Electrostatic dissipative shoes **ESD** Environmental Class II tested according to **EN 61340-4-3/4-5/5-1**.
- ❖ Microfibre upper, easily washable with soapy water, good splash resistance **TPU insert** built-in to the laces, ensuring an effective heel grip, enhanced alignment of the foot in the shoe and protection against any sprains.
- ❖ **3D ROMA** mesh upper lining, micro-ventilated technology, smooth appearance, 3-layer structure combining textile mesh, foam and reinforcing grid. High mechanical resistance (abrasion and tearing) and quick drying.
- ❖ Lined and padded tongue for better protection of the instep, combined with two side gussets to prevent any material from getting inside the shoe.
- ❖ Ergonomic padded collar with compact flexible foam for extra comfort and better ankle and Achilles tendon protection.
- ❖ **Xtensible™** Quicklace fastening system with no lacing: elastic lace fitted with an adjustable **Stop-Lace** quick tight lace.
- ❖ **Soft+ Gel** footbed made of **BASF Dynamic PU** with heat sensitive memory foam and acts over the entire surface of the foot, cushions pressure points, improves weight distribution and shock absorption caused by impact with the ground. Anatomical, breathable and fitted with the **Link ESD™** system, static electricity dissipater (Patent pending).
- ❖ This is a **DGUV 112-191** certified model, with the option of swapping the hygienic insole provided for a **SECOSOL®** orthopaedic insole.
- ❖ Heel stiffener to reinforce the heel seat.
- ❖ Innovative **J-Energy** sole in bi-ingredient **PU** / and **BASF Infinergy® E-TPU** (Expanded Thermoplastic PolyUrethane) insert, with a remarkable capacity to reproduce more than **55%** of the energy accumulated while walking in order to reduce fatigue and to prevent RSIs to the legs.



Slip resistance tests results EN Standard ISO 20345:2012	
Test ground : Ceramic / NaLS (Sodium lauryl sulfate)	
A- Heel to the front	0,62 (>0,32)
B- Front to back	0,48 (> 0,28)
Additional requirement SR : Ceramic /Glycerin	
C - Heel to the front	0,23 (>0,18)
D- Front to back	0,19 (>0,13)

- Polyurethane outer sole.
- **E-TPU insert** at low density of 0.25.
 - As elastic as rubber but lighter.
 - High resistance to abrasion and stretching..
 - Good chemical resistance..
 - Long-term durability in a wide temperature range.
 - **Dynamic performance in 3 phases: Shock Absorption - Accumulation of energy - Dynamic Return**



www.jallatte.com

Weight	Gross weight (42) : 1116 g / Net weight (42) : 900 g			
Size	35 to 39	40 to 42	43 to 45	46 to 48
Packaging	5 pairs	10 pairs		5 pairs
Box shoes (mm)	340 x 210 x 133		340 x 245 x 133	
Cartons (mm)	687 x 226 x 350	687 x 432 x 348	689 x 511 x 351	689 x 226 x 351